



GENERAL NOTES

Where at any time, any vehicle, equipment, workers or their activities will encroach in the area between the center line and a line 600 mm (24") outside the edge of pavement.

* Cones at 8 m (25') centers for 105 m (350'). Additional cones may be placed at 15 m (50') centers. When drums or barricades are used. The interval between devices may be doubled.

** Flaggers shall be positioned in advance of the work operation and remain there until the lane is open to traffic.

When the distance between successive patches is less than 450 m (1500'), the entire operation may be considered as one work area for flagging and signing purposes. When the distance between successive patches exceeds 450 m (1500'), additional warning signs, flaggers, and taper shall be used.

All dimensions are in millimeters (inches) unless otherwise shown.

SYMBOLS

- Work area
- Sign
- Barricade or drum
- Cone, drum or barricade
- Flagger with traffic control sign

TYPICAL APPLICATIONS

Patching
Utility operations
Storm sewer
Culvert
Cable placement

Illinois Department of Transportation	
APPROVED _____ January 1, 2000 ENGINEER OF OPERATIONS	ISSUED 1-1-97
APPROVED _____ January 1, 2000 ENGINEER OF DESIGN AND ENVIRONMENT	

DATE	REVISIONS
1-1-00	Rev. TYPICAL APPLICATION & detail of patch area.
1-1-97	Renum. Standard 2303-10. Deleted orange flags.
	Revised 2nd GN.

LANE CLOSURE, 2L, 2W, DAY ONLY
ON-RD TO 600 mm (24") OFF-RD
FOR SPEEDS ≥ 45 MPH

STANDARD 701201-01